



SRD34F



SRD34H



SRD34Y

Reversierbare Rüttelplatten

Reversible Vibrating Plate Compactors

SR34H, SRD34F, SRD34H, SRD34Y

Pluspunkte:

- ✘ Mit unterschiedlicher Zentrifugalkraft lieferbar
- ✘ überzeugend speziell beim Einsatz auf Pflaster und Bitumen
- ✘ Kunststoffplatte
- ✘ Verdichtung in regelbarer Geschwindigkeit Vor- und Rücklauf oder auf der Stelle möglich
- ✘ Langlebigkeit
- ✘ leichte, unproblematische Handhabung
- ✘ Kurbelstart, Seilstart
- ✘ Sehr niedrige Bauhöhe
- ✘ Benzin- oder Dieselmotor lieferbar

Special Features:

- ✘ Available with different centrifugal force
- ✘ for paving and asphalt laying
- ✘ Synthetic plates for all sizes available
- ✘ Compaction with adjustable forward-reverse speed or point compaction
- ✘ Long service life
- ✘ Easy to operate
- ✘ Crank start, Rope start
- ✘ Low height
- ✘ Available with Gasoline or Diesel Engines



DELKO

DELKO GmbH, Uhinger Straße 93, D-73095 Albershausen
 Telefon +49 7161 50097-0, Fax +49 7161 50097-90
 Internet: www.delko-gmbh.de e-mail: info@delko-gmbh.de

Technische Daten		SR34H	SRD34F	SRD34H	SRD34Y
Zentrifugalkraft	kN	34	34	34	34
Frequenz	Hz	80	84	84	84
Arbeitsgeschwindigkeit	m/min	0-24/22/20	0-26/24/22	0-26/24/22	0-26/24/22
Flächenleistung bis	m ² /h	562 / 634	580/670/740	600/690/760	580/670/740
Tiefenwirkung bis	cm	40	45	45	45
Gesamtlänge	mm	1490	1490	1490	1490
Höhe (ohne Lenker)	mm	710	800	800	800
Länge Bodenwanne	mm	810	810	810	810
Breite Bodenwanne	mm	390 / 480 / 580	390 / 480 / 580	390 / 480 / 580	390 / 480 / 580
Gewicht ca.	kg	174 / 181 / 188	218 / 225 / 232	210 / 217 / 224	212 / 219 / 226

Motor		Honda GX160	Farymann 18 D	Hatz 1B30	Yanmar L70
4-Takt Benzin		●	Diesel	Diesel	Diesel
EPA-2004		●		○	○
Leistung	kW	3,7	4,2	4,6	4,2
Drehzahl	1/min	3300	3000	3000	3600
Verbrauch	l/h	1,2	1,0	1,1	1,1
Tankinhalt	l	3,6	4,0	4,0	3,5

Standard ● / [Optional ○]

DELKO GmbH - (2007-01-16) - Technische Änderungen vorbehalten

Technical Data		SR34H	SRD34F	SRD34H	SRD34Y
Centrifugal force	kN	34	34	34	34
Vibrating frequency	Hz	80	84	84	84
Working speed	m/min	0-24/22/20	0-26/24/22	0-26/24/22	0-26/24/22
Area output up to	m ² /h	562 / 634	580/670/740	600/690/760	580/670/740
Compaction depth up to	cm	40	45	45	45
Total length	mm	1490	1490	1490	1490
Height (without handle bar)	mm	710	800	800	800
Length of base plate	mm	810	810	810	810
Width of base plate	mm	390 / 480 / 580	390 / 480 / 580	390 / 480 / 580	390 / 480 / 580
Weight aprox.	kg	174 / 181 / 188	218 / 225 / 232	210 / 217 / 224	212 / 219 / 226

Engine		Honda GX160	Farymann 18 D	Hatz 1B30	Yanmar L70
4-stroke gasoline		●	Diesel	Diesel	Diesel
EPA-2004		●		○	○
Output	kW	3,7	4,2	4,6	4,2
Speed	1/min	3300	3000	3000	3600
Consumption	l/h	1,2	1,0	1,1	1,1
Tank capacity	l	3,6	4,0	4,0	3,5

Standard ● / [Option ○]

DELKO GmbH - (2007-01-16) - Technical data subject to changes