

Forward Vibratory Plates

The new JCB forward plate range includes the 300mm, 400mm and 500mm models. All models are fitted with Honda engines and can be specified with additional options to suit the customer.



Features

- Low vibration levels for improved operator comfort
- Improved serviceability from remote oil drain
- Robust, durable design with cast base plate and full engine protection frame
- Fast travel and high productivity
- Extensive options available including sprinkler, transport wheels and paving pad
- Folding handle for easy storage and transport.
- Hand throttle

Details

Model number		FP1030W	FP1540W	FP1550W
HAV Levels (triple axis)	m/s ²	2.56	1.92	1.80
Weight	kg	62 – 75kg	91 – 110kg	100 – 119kg
Base plate size WxL	mm	300 x 344.8	400 x 394.8	500 x 394.8
Centrifugal force	kN	10	15	15
Frequency	Hz	100	100	100
Engine		Honda GX100	Honda GX160	Honda GX160
Fuel		Petrol	Petrol	Petrol
Power	Kw (hp)	2.1 (2.8)	3.6 (4.8)	3.6 (4.8)
Accessories		12L Sprinkler System Paving Pad	19L Sprinkler System Transport Wheels Paving Pad	19L Sprinkler System Transport Wheels Paving Pad
		Hand Throttle As Standard	Hand Throttle As Standard	Hand Throttle As Standard